



S O N E I L

6033 Shawson Dr., Unit 29, Mississauga, Ontario, Canada L5T 1H8
Ph.: (905) 565-0360 Fax: (905) 565-0352 <http://www.soneil.com>

Revision No.: R04

Specification of Battery Charger

MODEL : 1230 R

12V / 15A LEAD ACID BATTERY CHARGER



Subject to change without prior notice, please feel free to contact us for latest information.

1. General

Battery Charger 1230R 170*90*63mm is cooled by 12VDC ball-bearing fan with forced air, can work normally under 14.7Vdc/15A, with reverse polarity protection.

2. Main product specification

Max. output power	Input voltage	Output voltage	Output current range	Combined regulation
230W	230Vac	+14.7+/-0.2Vdc	14.5-15.5A	+/-0.2V

3. Environmental condition

No.	Item	Technical specification	Remark
1	Humidity	5~95%	With package
2	Altitude	≤3000m	Work normally
3	Cooling	The power supply is cooled by 12VDC ball-bearing fans forced air	Working under full load

4. Electrical characteristics

4.1 Input characteristic

No.	Item	Technical specification	Remark
1	Input voltage range	200 ~ 264 Vac	230Vac single input
2	AC input voltage frequency	50 Hz	
3	Max input current	1.5A	Vin=200Vac, rated load

4.2 Output characteristic

No.	Item	Technical specification	Remark
1	Fast charge voltage	14.7+/-0.2Vdc	
2	Floating voltage	13.8Vdc	
3	Constant current	15A	
4	Switch current	3.0A	
5	Power efficiency	≥88%	Vin=200 Vac, rated load
6	Output inhibit voltage	13.7~14.0V	For powering electric vehicle controller only
7	Output inhibit current	50~100mA	

4.3 Protection characteristics

No.	Item	Technical specification	Remark
1	Over voltage protection		
2	Software over voltage protection	The charger software limits the maximum output voltage to a level suitable for the connected battery system	
3	Thermal protection	N/A	
4	Current limiting protection	16.5A	At CC mode
5	Short circuit protection	Short circuit protection should be automatically recovery after remove the condition	

4.4 Charging indicator

No.	Item	Status	Remark
1	Power on	LED1: red	
2	Charging	LED2: red	
3	Fully charged	LED2: green	

5. Safety & EMC

No.	Item	Standard(or test condition)	Remark
1	Electric strength test	Input-output 1500Vac/10mA/1min	No breakdown
2	Isolation resistance	Input-ground $\geq 10\text{Mohm}@500\text{Vdc}$	
		Output-ground $\geq 10\text{Mohm}@500\text{Vdc}$	
3	Leakage current	$< 3.5\text{mA}$	$V_{in}=264\text{Vac}$
4	Safety	CE /UL compliant	
5	EMC	EN55022:1998+A1:2000+A2:2003 EN55024:1998+A1:2001+A2:2003 (EN61000-4-2:1995+A1:1998+A2:2001 EN61000-4-3:2002 EN6100-4-4:1995+A1:2000+A2:2001 EN61000-4-5:1995+A1:2000 EN61000-4-6:2001 EN61000-4-11:2001)	
6	LVD	EN60335-1:2002+EN60335-2-29:2002	

Remark: Discrimination A- Function OK under technical requirement range;

Discrimination B- Function temporarily debasement without reposition and halt is allowed;

Discrimination R – Physical damage or failure of equipment are not allowed, but damage of protection device (fuse) caused by interference signal of outside is allowed, and the whole equipment can work normally after replacement of protection device and reset of running parameter

6. Environmental testing requirements

No.	Item	Technical specification	Remark
1	High temperature ambient operating	+40°C	Features ok
2	Low temperature ambient operating	-10°C	Features ok
3	High temperature storage	+70°C	Work normally after recovery under normal temperature for 2hours
4	Low temperature storage	-40°C	Work normally after recovery under normal temperature for 2hours
5	Random vibration	20Hz to 2000Hz 3Grms 20hours per axis	
6	Repetitive shock	40g peak 3 orthogonal axes, 3+ and 3-	

		in each axis, 11ms pulse width	
7	Thermal shock	-35°C to 75°C, < 3min transition, 2.5hours dwell, 200cycle	
8	Drop test	BS EN60068-2-32:1993 TEST ED: free fall appendix B	

7. Mechanical characteristics

Outline dimension: L*W*H=170*90*63mm

Input socket: meets IEC standard;

Output wire: 12AWG, 2.5mm², brown (+ve) & blue (-ve), 1.5m length; thick insulation.

Weight: 1.3Kg



8. Package, transportation & storage

8.1 Package:

There is product name, model, name of manufacturer, safety approval, serial number, User Manual and packing list in the package box.

8.2 Transportation:

Suit for transportation by truck, ship and plane, the products should be shielded by tent from sunshine, and loaded and unloaded carefully.

8.3 Storage:

Products should be stored in package box when it is not used. And warehouse temperature should be -40~70°C, and relative humidity is 5~95%. In the warehouse, there should not be harmful gas, inflammable, explosive products, and corrosive chemical products, and strong mechanical vibration, shock and strong magnetic field affection. The package box should be above ground at least 20cm height, and 50cm away from wall, thermal source, and vent. Under this requirement, product has 2years of storage period, and should be rechecked when over 2years.

9. Reliability requirements








MTBF(standard, environmental temperature, load requirement) ≥50K hours; testing condition: 25°C, full load, testing proved value.

10. Charger wiring

10.1 A spark often on first connection of the charge to the battery terminals due to charging the internal output capacitors, this is normal and should not lead to undue concern, care should be taken to ensure the battery vent caps are closed and there are no flammable object in the vicinity of where the connection will be made

10.2 The charger has been calibrated to take account of the voltage drop in the DC output cables during operation, to prevent the possibility of over or under charging of the battery it is recommended the DC output cable are connected directly to the battery without modification. We are able to customize cable length and connections for volume customers with specific requirements.

11. Label

<p>SONEIL-CANADA Tel: 905-565-0360 Fax: 905-565-0352 www.soneil.com MODEL 1230R PATENT PENDING</p>   	<p>AC Input: 230V AC 60/50Hz Max. Input Current: 1.5A at 200V ac Input DC Output: 12V/15.0 A Constant</p>	<p>Charging Indicator: LED1: Red Power On LED2: Red Charging LED2: Green Charged</p> <p>DC Output Wire: Brown wire: DC(+) Blue wire: DC(-)</p>	<p>Serial No.:</p>	<p>Caution:</p> <ul style="list-style-type: none"> ■ Risk of electric shock. Do not expose to liquid, vapor or rain. ■ Charge only lead-acid type rechargeable batteries. Other types of batteries may burst causing personal injury and damage. ■ Slow Blow AC Fuse: 250V10A    
--	---	---	--------------------	---

12. Charging Curve

(Refer to attachment)