


ECO-FRIENDLY ADVANCE TECHNOLOGY BATTERY




12- EFSL -76, 12V 76Ah@20HR

DIMENSION



CYCLE LIFE GRAPH (25°C/77°F)




TEMPERATURE & FLOAT SERVICE LIFE



SPECIFICATIONS

Nominal Voltage	12V	
Rated Capacity (20 hour rate)	76AH	
Dimension	Total Height (with terminals)	215 mm
	Height	210mm
	Length	260mm
	Width	169mm
Weight	Approx.	23 Kg/50 lbs.
Capacity (77°F/25°C)	10 hour rate (7.0A)	70AH
	5 hour rate (13.2A)	66AH
Internal Resistance (77°F/25°C)	Full Charged Battery	≤8.0mΩ
Self-Discharge (77°F/25°C)	After 3 months Storage	95%
	After 6 months storage	85%
	After 12 months storage	80%
Max Discharge Current (77°F/25°C)	600A(5S)	
Terminal	Standard	F3
	Optional	
Charging (Constant Voltage)	Cycle	14.4V-14.7V (77°F/25°C)
	Float	13.5V-13.8V (77°F/25°C)

CHARGE CHARACTERISTIC 25°C (77°F)



Soneil Chargers Recommended


CONSTANT CURRENT DISCHARGE CHARACTERISTICS UNITS AMPERES (25°C/77°F)

End Voltage per cell (V)	Time (Mins)														
	5	15	30	45	60	120	180	240	300	360	480	600	720	1200	1440
1.60	256.87	135.94	82.14	59.88	48.23	27.63	20.07	15.74	13.42	11.41	8.70	7.24	6.08	3.96	3.23
1.67	238.73	131.49	80.92	59.47	48.15	27.51	19.71	15.66	13.23	11.33	8.69	7.16	6.07	3.95	3.22
1.70	236.29	129.47	80.11	58.67	47.75	27.27	19.58	15.58	13.03	11.21	8.66	7.16	6.05	3.93	3.22
1.75	216.47	125.41	79.31	58.27	46.94	26.75	19.50	15.38	12.91	11.13	8.62	7.08	6.02	3.92	3.21
1.80	194.21	117.32	76.06	56.64	45.72	26.34	19.42	15.34	12.75	11.01	8.58	7.00	5.99	3.78	3.20
1.83	185.64	107.63	74.86	54.63	43.70	26.10	18.65	14.69	12.46	10.60	8.40	6.72	5.75	3.74	3.16
1.85	173.96	104.38	70.00	52.60	42.48	25.05	18.17	14.48	12.14	10.25	8.30	6.64	5.66	3.70	3.14


DISCHARGE DATA WITH CONSTANT POWER UNITS: WATTS PER CELL (25°C/77°F)

End Voltage per cell (V)	Time (Mins)														
	5	15	30	45	60	120	180	240	300	360	480	600	720	1200	1440
1.60	429.24	238.70	153.74	112.07	90.15	52.19	38.15	30.22	25.53	21.93	16.91	14.00	11.77	7.85	6.43
1.67	408.61	235.05	147.52	111.26	89.85	52.19	37.67	30.18	25.53	21.89	16.91	13.96	11.77	7.85	6.43
1.70	406.18	233.43	147.18	111.26	89.41	51.78	37.45	30.07	25.12	21.73	16.79	13.84	11.65	7.81	6.43
1.75	378.27	230.60	146.79	111.26	89.01	51.38	37.05	30.02	25.04	21.56	16.71	13.74	11.65	7.81	6.39
1.80	347.12	218.87	144.43	109.23	88.60	51.38	36.55	29.94	24.88	21.56	16.67	13.67	11.65	7.61	6.39
1.83	334.98	201.07	143.22	106.00	84.96	50.98	35.95	28.93	24.60	20.88	16.67	13.27	11.45	7.53	6.35
1.85	310.30	196.62	133.10	101.96	82.53	49.76	35.40	28.56	23.91	20.47	16.02	13.15	11.25	7.44	6.31

FLOAT SERVICE LIFE CURVE GRAPH



TEMPERATURE AND DISCHARGE CAPACITY



“Specifications subject to change without notice “

Domestic & International Sales: Tel: +1 905 565 0360 Fax: +1 905 799 6821, Email: info@soneil.com

Corporate Office: 180 Advance Blvd, Unit 3, Brampton, Ontario, Canada L6T 4J4



www.soneil.com