

Accuracy, Quality,  
Performance

## Battery Gauges

**SONEIL**  
ELECTRONICS

### Standard Features

- ▶ LED Flash Light for low battery charge
- ▶ At 70% depth of discharge, a flashing LED signals an “energy reserve” alert
- ▶ At 80%, alternately flashing LEDs provides an “empty” status warning with an Alarm Beep option
- ▶ Customizable LCD Colour display to match your panel

### Additional Wi-Fi Enabled Features

- ▶ Configure Peer– Sync the gauge SSID or connect it to the company’s network to control remotely.
- ▶ Up to 4 analog signals (Voltage, Current, Temperature, etc.)
- ▶ Monitor and control multiple gauges with unlimited storage.
- ▶ 2 embedded cut-off 5 Amp relays to control and sustain energy.
- ▶ All set ups are done through the web browser and do not require a software installation.

★ For more Wi-fi options, please contact [info@soneil.com](mailto:info@soneil.com)

### Electrical Specifications

- ▶ Battery Voltages: 12V, 24V, 36V, 48V
- ▶ Operating Voltages: +25% to -50% of nominal Voltage
- ▶ Operating Temperature: -40°C to +85°C



*Custom Design (LED Display, Shape, Size, Colour, and Other Features)*



**Head Office** 

3-180 Advance Blvd., Brampton, Ontario, Canada, L6T 4J4  
Tel. +1 905 565 0360, Fax +1 905 799 6821  
Email: [info@soneil.com](mailto:info@soneil.com)

[www.soneil.com](http://www.soneil.com)

**UK Office** 

187 Shakespeare Ave, Hayes, Middlesex UB4 0BH  
Tel. +44 0 772 555 2917, Fax +44 0 208 573 6717  
Email: [info@soneil.com](mailto:info@soneil.com)